



ARGUS
STEEL PRODUCTS

P.O. Box 25133 | Richmond, Virginia 23260
 (804) 359-4840 • (800) 368-2082
 Fax (804) 358-3415
 sales@argussteel.com | www.argussteel.com

WIRE CLOTH • PERFORATED METAL • EXPANDED METAL • GRATING

Standard(Raised) Expanded 304 Stainless Steel

Style	WT/SF	Design		Openings		Strand		Overall Thickness	Open Area
		SWD	LWD	SWO	LWO	Thickness	Width		
1/4 #18	.085#	.312"	1.000"	.191"	.558"	.044"	.072"	.130"	54%
1/2 #18*	.620#	.480"	1.200"	.382"	.913"	.044"	.074"	.140"	69%
1/2 #16*	.760#	.480"	1.200"	.362"	.965"	.055"	.074"	.145"	69%
1/2 #13*	1.490#	.480"	1.200"	.306"	.817"	.090"	.094"	.180"	60%
3/4 #16*	.470#	.923"	2.000"	.816"	1.632"	.055"	.096"	.180"	80%
3/4 #13*	.760#	.923"	2.000"	.784"	1.494"	.090"	.096"	.190"	80%
3/4 #9*	1.760#	.923"	2.000"	.703"	1.484"	.134"	.144"	.260"	69%
1-1/2 #16*	.380#	1.330"	3.000"	1.243"	2.566"	.055"	.104"	.200"	84%
1-1/2 #13*	.580#	1.330"	3.000"	1.228"	2.517"	.090"	.104"	.210"	85%
1-1/2 #9*	1.210#	1.330"	3.000"	1.105"	2.366"	.134"	.144"	.250"	79%

Please note: Standard sheet size is 4'x8'. Please contact us with other size requirements.

* Denotes material is also available in T316 Stainless