



ARGUS
STEEL PRODUCTS

P.O. Box 25133 | Richmond, Virginia 23260
 (804) 359-4840 • (800) 368-2082
 Fax (804) 358-3415
 sales@argussteel.com | www.argussteel.com

WIRE CLOTH • PERFORATED METAL • EXPANDED METAL • GRATING

Standard(Raised) Expanded Aluminum

Style	WT/SF	Design		Openings		Strand		Overall Thickness	Open Area
		SWD	LWD	SWO	LWO	Thickness	Width		
1/2 x .051"	.260#	.500"	1.200"	.410"	.890"	.050"	.078"	.130"	69%
1/2 x .081"	.400#	.500"	1.200"	.362"	.827"	.080"	.087"	.170"	65%
3/4 x .051"	.160#	.923"	2.000"	.866"	1.692"	.050"	.087"	.160"	81%
3/4" x .081"(L)	.280#	.923"	2.000"	.838"	1.547"	.080"	.114"	.190"	76%
3/4 x .081"	.400#	.923"	2.000"	.781"	1.551"	.080"	.154"	.290"	65%
3/4 x .125"	.570#	.923"	2.000"	.695"	1.508"	.125"	.144"	.260"	69%
1-1/2 x .081"	.220#	1.330"	3.000"	1.234"	2.516"	.080"	.124"	.230"	81%
1-1/2 x .125"	.420#	1.330"	3.000"	1.172"	2.397"	.125"	.156"	.285"	76%

Please note: Standard sheet size is 4'x8'. Please contact us with other size requirements.