



ARGUS

STEEL PRODUCTS

INQUIRIES

P.O. Box 25133 | Richmond, Virginia 23260
 (804) 359-4840 • (800) 368-2082
 Fax (804) 358-3415

sales@argussteel.com | www.argussteel.com

WIRE CLOTH • PERFORATED METAL • EXPANDED METAL • GRATING

Common Wire Cloth Sizes

Mesh Count Per Inch	Wire Dia.	Mesh Opening	Open Area	Lbs/SqFt
1	.063"	.937"	87.80%	0.26
1	.080"	.920"	84.60%	0.41
1	.105"	.895"	80.10%	0.71
1	.120"	.880"	77.40%	0.93
1	.135"	.865"	74.80%	1.18
2	.047"	.453"	82.10%	0.28
2	.063"	.437"	76.40%	0.51
2	.080"	.420"	70.60%	0.83
2	.105"	.385"	62.40%	1.44
2	.120"	.380"	57.80%	1.9
3	.047"	.286"	73.60%	0.43
3	.063"	.270"	65.60%	0.78
3	.080"	.253"	57.60%	1.26
4	.032"	.218"	76.00%	0.26
4	.035"	.215"	74.00%	0.32
4	.047"	.203"	65.90%	0.58
4	.063"	.187"	56.00%	1.05
4	.080"	.170"	46.20%	1.72
5	.032"	.168"	70.60%	0.33
5	.041"	.159"	63.20%	0.55
5	.047"	.153"	58.50%	0.73
6	.028"	.139"	69.60%	0.31
6	.035"	.132"	62.70%	0.48
6	.047"	.120"	51.80%	0.88
7	.028"	.115"	64.80%	0.36
7	.035"	.108"	57.20%	0.57
8	.025"	.100"	64.00%	0.33
8	.028"	.097"	60.20%	0.41
8	.032"	.093"	55.40%	0.54
8	.035"	.090"	51.80%	0.65
8	.047"	.078"	38.90%	1.21
10	.020"	.080"	64.00%	0.26
10	.025"	.075"	56.30%	0.41
10	.032"	.068"	46.20%	0.69
10	.035"	.065"	42.30%	0.83
10	.047"	.053"	28.10%	1.48
12	.018"	.065"	60.80%	0.26
12	.023"	.060"	51.80%	0.42
12	.028"	.055"	43.60%	0.64
12	.032"	.051"	37.50%	0.84
12	.035"	.048"	33.20%	1.02
14	.009"	.062"	76.40%	0.07
14	.017"	.054"	57.20%	0.27
14	.020"	.051"	51.00%	0.37

Mesh Count Per Inch	Wire Dia.	Mesh Opening	Open Area	Lbs/SqFt
16	.009"	.0535"	73.30%	0.09
16	.011"	.0515"	67.90%	0.13
16	.016"	.0465"	55.40%	0.27
16	.018"	.0445"	50.70%	0.35
16	.028"	.0345"	30.50%	0.84
16	.035"	.0275"	19.40%	1.37
18 x 14	.009"	.0466"	70.20%	0.10
18	.015"	.0406"	53.40%	0.27
18	.017"	.0386"	48.30%	0.35
20	.009"	.0410"	67.20%	0.11
20	.014"	.0360"	51.80%	0.26
20	.016"	.0340"	46.20%	0.34
20	.018"	.0320"	41%	0.44
20	.023"	.0270"	29.20%	0.71
22	.0135"	.0320"	49.60%	0.27
24	.0075"	.0342"	67.20%	0.09
24	.014"	.0277"	44.20%	0.32
26	.0075"	.0310"	64.80%	0.10
26	.011"	.0275"	51.10%	0.21
28	.0075"	.0282"	62.40%	0.10
28	.010"	.0257"	51.80%	0.19
30	.0065"	.0268"	64.80%	0.10
30	.010"	.0233"	48.90%	0.20
30	.012"	.0213"	40.80%	0.29
32	.0065"	.0248"	62.70%	0.10
32	.009"	.0223"	60.90%	0.17
35	.011"	.0176"	37.90%	0.29
40	.0085"	.0165"	43.60%	0.20
40	.010"	.0150"	36.00%	0.28
50	.0075"	.0125"	39.10%	0.19
50	.009"	.0110"	30.30%	0.28
60	.0045"	.0122"	53.30%	0.06
60	.0065"	.0102"	37.50%	0.17
60	.0075"	.0092"	30.60%	0.24
70	.0065"	.0078"	29.80%	0.21
80	.0055"	.0070"	31.40%	0.17
80	.007"	.0055"	19.40%	0.25
100	.0045"	.0055"	30.30%	0.14
120	.0026"	.0058"	47.30%	0.05
120	.0037"	.0046"	30.10%	0.10
150	.0026"	.0041"	37.40%	0.07
180	.0018"	.0038"	46.00%	0.05
180	.0023"	.0033"	34.70%	0.07
200	.0021"	.0029"	33.60%	0.06

More specifications are available. Please contact us for further information.